












DANE TECHNICZNE	S235		S130		S145		KS260		SV10	SP235 / KX135	
											
	<b>S235E</b>	<b>S235EP</b>	<b>S130L</b>	<b>S130PL</b>	<b>S145EL</b>	<b>S145EPL</b>	<b>KS260E</b>	<b>KS260EP</b>	<b>SV10</b>	<b>SP235</b>	<b>KX135</b>
APP Nr	141400	141410	141010	141020	141100	141110	141200	141300	141420	141550	141500
Napięcie [V]	230	230	230	230	230	230	230	230	230	-	-
Ciśnienie robocze [bar]	-	6	-	6	-	6	-	6	-	6	6
Moc [W]	1100	1100	1200	1200	1200	1200	2 x 1000	2 x 1000	1150	-	-
Max. moc obciążenia [W]	2500	2500	2400	2400	2400	2400	2 x 800    1 x 1600	2 x 800    1 x 1600	1 x 1000	-	-
Automatyka	EL	EL / PN	EL	EL / PN	EL	EL / PN	EL	EL / PN	-	-	-
Podciśnienie mm [H <sub>2</sub> O]	1700	1700	2000	2000	2000	2000	2000	2000	1600	1900	1900
Wydajność ssania [m <sup>3</sup> /h]	180	180	200	200	200	200	260	260	-	100	100
Pojemność worka na pył [kg]	5	5	5	5	5	5	7	7	3,5	7	7
Pojemność zasobnika [kg]	35	35	30	30	45	45	65	65	-	-	-
Głośność [dB(A)]	75	75	70	70	67	67	72	72	75	-	-
Waga [kg]	8	8	10	10	13	13	26	26	6,5	8	30
Max przepływ powietrza [l/min]	-	1500	-	1450	-	1450	-	1450	-	1000	1000